

Product	Description	Technical data sheet
LUVOCOM 3F PP GF 50282 BK	PP, 30 % glass fibers, black	
LUVOCOM 3F PP CF 9928 BK	PP, 20 % carbon fibers, ESD, black	
LUVOCOM 3F PP CF 50709 BK	PP, 20 % carbon fibers, electrically conductive $<10^3$ Ohm	
LUVOCOM 3F PET CF 9780 BK	PP, 15 % carbon fibers, black	Download
LUVOCOM 3F PA12 CF 9798 BK	PA12, 15 % carbon fibers, ESD	
LUVOCOM 3F PAHT CF 9742 BK	High-temperature polyamide, 15 % carbon fibers	
LUVOCOM 3F PAHT CF 9743 BK	High-temperature polyamide, 25 % carbon fibers	
LUVOCOM 3F PAHT CF 9806 BK	PA12, 10 % carbon fibers, ESD	
LUVOCOM 3F PAHT CF 9891 BK	High-temperature polyamide, 15 % carbon fibers, low moisture uptake	
LUVOCOM 3F PPS 9937 BK	PPS compound, unreinforced, black, UL94 V0 flammability	
LUVOCOM 3F PPS GF 50300 BK	PPS, 10 % glass fibers, UL94 V0 flammability	
LUVOCOM 3F PPS CF 9938 BK	PPS, 15 % carbon fibers, EN45545-2 conformity, UL94 V0 flammability, black	
LUVOCOM 3F PPS CF 50353 BK	PPS, 30 % carbon fibers, electr. conductive $<10^3$ Ohm, UL94 V0 flammability	
LUVOCOM 3F PPS CF 50899 BK	PPS, 10 % carbon fibers, UL94 V0 flammability	Download
LUVOCOM 3F PEEK GF 9761 BK	PEEK, 30 % glass fibers, UL94 V0 flammability, black	
LUVOCOM 3F PEEK CF 9676 BK	PEEK, 15 % carbon fibers, NORSOK M710 qualified, UL94 V0 flammability	