

Product	Description	Technical data sheet
LUVOCOM 3F TPU 50289 NT	TPU compound, 85 Shore A, natural	
LUVOCOM 3F PLA HT 50593 WT	PLA, increased thermal resistance, natural (white)	
LUVOCOM 3F PA12 CF 50414 RD	PA12, 15 % carbon fibers, red	
LUVOCOM 3F PA12 CF 50415 BL	PA12, 15 % carbon fibers, blue	
LUVOCOM 3F PA12 CF 50416 GN	PA12, 15 % carbon fibers, grey	
LUVOCOM 3F PET CF 50474 GY/L	PET, 15 % carbon fibers, food compliant, grey	
LUVOCOM 3F PET CF 50474 RD/L	PET, 15 % carbon fibers, food compliant, red	
LUVOCOM 3F PET CF 50474 BL/L	PET, 15 % carbon fibers, food compliant, blue	
LUVOCOM 3F PAHT 9825 NT	High-temperature polyamide natural (white)	
LUVOCOM 3F PAHT 50588 BL/L	High-temperature polyamide, low moisture uptake, food compliant, detectable, blue	
LUVOCOM 3F PEI 50236 GY	PEI compound unreinforced, EN 45545-2 conformity, UL94 V0 flammability, grey	