

Product	Description	Technical data sheet
LUVOCOM 3F TPU 50289 NT	TPU compound, 85 Shore A, natural	
LUVOCOM 3F PLA HT 50593 WT	PLA, increased thermal resistance, natural (white)	
LUVOCOM 3F PP 9929 NT	PP compound, natural	
LUVOCOM 3F ABS 50624 NT	ABS compound, natural	
LUVOCOM 3F PAHT 9825 NT	High-temperature polyamide natural (weiß)	
LUVOCOM 3F PAHT 9936 L/BK	High-temperature polyamide, low moisture uptake, food compliant, detectable, black	Download
LUVOCOM 3F PAHT 9875 NT	High-temperature polyamide, low moisture uptake	
LUVOCOM 3F PEI 50236 GY	PEI-compound unreinforced, EN 45545-2 conformity, UL94 V0 flammability, grey	
LUVOCOM 3F PEKK 50082 NT	PEKK compound unreinforced, UL94 V0 flammability, natural	
LUVOCOM 3F PEEK 9581 NT MP	PEEK compound, NORSOK M710 qualified, micro pellet, UL94 V0 flammability	
LUVOCOM 3F PEEK 50260 NT	PEEK compound, NORSOK M710 qualified, standard pellet, UL94 V0 flammability	